

Powered by StarV3™

Advanced Performance

All units feature advanced RF functionality and processor optimization. Our drivers are proprietary and **built for performance**, not simply stock reference drivers used by others.

Full Spectrum Support

Our Cloaking Mode 5MHz and 10MHz channel spacing and widths deliver up to **4 times the number of useable non-overlapping channels** in each frequency band compared to 'normal' 802.11 systems. Bandwidth delivery exceeds 6meg at even the smallest channel size.

High Bandwidth

The Au400 is capable of delivering **up to 60 mbps** of compressible data in standard mode. Uncompressible data throughput exceeds 26 mbps in standard mode, and 43 mbps in turbo mode.

Unrivaled Feature Set

StarV3 delivers full routing capabilities including RIP, OSPF, and **high performance mesh networking** with OLSR. A full suite of QoS, security and management tools rounds out the StarV3 feature set with an **easy to use interface**.

Au400

Wireless Advanced Router Access Unit

The Au400 is a high performance multi-role 4 radio wireless advanced router access unit. Its power and versatility make it ideal for a wide range of complex access, mesh, or point to point network deployments.



Product Highlights

- Industry leading robust StarV3 powered operating system from StarOS.
- Operating at 533MHz it delivers the power to perform for all 4 radios simultaneously.
- Users can deploy any combination of four of our 5 available radios covering the complete 900MHz through 6GHz radio spectrum, and utilize the antennas of their choice on the 4 external N-Female connectors.
- Cloaking Mode enhanced channel widths and spacing delivers maximum network design versatility for large scale mesh and access networks.
- Our rugged hinged cast aluminum outdoor enclosure system provides both ease of use and dependable performance in the most challenging environments. The integrated articulating sector antenna mount and optional integrated omni antenna(s) allow for maximum deployment flexibility.
- The external LED indicator provides easy visual verification of overall unit operational status.
- Push button reboot with restore to factory defaults functionality eliminates the need to return misconfigured and locked units for reprogramming.
- The onboard power system protects the unit against transients and overvoltage events on both the power and Ethernet systems. It dynamically delivers up to 7.5 watts of power to fully drive even the most hungry high performance radios.
- Extended operating temperature exceeding -20C through 70C .
- Dual surge protected Ethernet ports with Auto MDI/MDIX and full POE support from our switching power supply system.



Wireless Networking Solutions. Ours Works.™



Au400
Optional Radios

Each Au400 Wireless Advanced Router access unit is available with the following choice of supported radios:

- 900MHz 700mW
- 2.4GHz 20dBm SuperG
- 2.4 & 4.9/5GHz 20dBm SuperAG
- 2.4 & 4.9/5GHz 23dBm SuperAG
- 2.4 GHz 26dBm SuperG

Additional frequencies are also available. Contact us with your specific frequency needs.



Applications

- Metropolitan scale MESH networks
- Traffic management systems
- Public safety access networks
- Video surveillance systems
- Campus networks
- Carrier backbones and extensions
- Corporate security systems
- WISP access networks
- Homeland security networks

- **Unsurpassed deployment versatility** in access, point to point, and mesh configurations. Each of the 4 radios is independently configured for the role and frequency range you require.
- Au400 access units are fully 802.11 standards compliant and interoperable in your standards compliant network today; **easily configured** to take full advantage of the powerful StarV3 proprietary feature set in a homogenous StarV3 network.
- StarV3 **Enhanced Signal Processing** implementations coupled with our unique channel spacing in Cloaking Mode increase signal survivability in polluted (urban) environments. The same signal processing also increases weak link stability making marginal links profitable.
- Star V3 enhancements deliver **reduced latency and jitter** for significantly improved VoIP, video, gaming—and overall improved network performance compared to other systems available today.
- All customers receive **total service and support** with their configuration and deployment issues. We treat customer networks like they were our own.

Operational Features

User Interface

- ⇒ Secure SSH
- ⇒ Telnet client
- ⇒ Command Line, with factory default reset

Access Layer Density

- ⇒ Up to 250 users per radio; 50 users per radio recommended

Security

- ⇒ Advanced firewall functionality with familiar Linux syntax or custom parser
- ⇒ StarV3 Cloaking Mode channel spacing
- ⇒ RADIUS client and server functionality
- ⇒ MAC address filtering and authentication with both local list and radius control
- ⇒ WPA1 and WPA2 with full radius control
- ⇒ TKIP and AES ciphers
- ⇒ 40, 104, and 128 bit WEP
- ⇒ NAT and static NAT support
- ⇒ IPMAP
- ⇒ Remote system logging

Routing Functionality

- ⇒ Mesh Networking with high performance OLSR
- ⇒ DHCP server and client with dynamic leases

Routing Functionality (cont...)

- ⇒ IEEE 802.11d bridging
- ⇒ Dynamic WDS support for true transparent bridging
- ⇒ High performance learning bridge with optional Spanning Tree Protocol
- ⇒ IEEE 802.1q VLAN
- ⇒ RIPv1 and v2, and OSPFv2 support
- ⇒ NAT and static NAT
- ⇒ Policy (source and purpose based) and static (destination based) routing support
- ⇒ VPN via proprietary distribution system with secure Ethernet over IP tunnels for up to 20 virtual VPN servers per unit
- ⇒ Multiple IP addresses per interface

Quality of Service

- ⇒ Full layer 2 and layer 3 traffic prioritization
- ⇒ Layer 7 filtering and shaping
- ⇒ Group, subnet, user, and protocol-based bandwidth shaping and prioritization with bandwidth fallback and parent class sharing
- ⇒ Simple asymmetrical/symmetrical bandwidth shaping option
- ⇒ Packet Aggregation for improved VoIP jitter and gaming latency



Wireless Networking Solutions. Ours Works.™

Technical Specifications

Radio Operation

- ⇒ Each radio independently configured and controlled
- ⇒ Full operating frequency range of currently supported radios
 - 870 - 950 MHz
 - 2312 - 2737 MHz
 - 4900 - 6120 MHz
- ⇒ Channel spacing
 - 40 MHz turbo
 - 20 MHz
 - 10 MHz
 - 5 MHz
- ⇒ Custom Frequency Scan Lists
- ⇒ Radio disable functionality

Wireless

- ⇒ Standards
 - IEEE 802.11a/b/g
 - IEEE 802.11d
 - IEEE 802.11e
 - IEEE 802.11h
 - IEEE 802.11i
- ⇒ Enhanced StarV3 Mode
- ⇒ Sensitivity
 - 2.4GHz = -92 dBm @ 1Mbps; -70 dBm @ 54Mbps
 - 5GHz = -90dBm @ 6Mbps; -70 dBm @ 54Mbps
- ⇒ Connection Rates
 - 108, 96, 72, 54, 48, 36, 24, 18, 12, 11, 9, 6, 5.5, 2, 1 Mbps
- ⇒ Advanced Features
 - Extended range with advanced digital signal processing
 - Weak signal processing and enhancement
 - Advanced Rate Control for Error Correction support
 - Adaptive Radio (AR/ANI) support
 - Enhanced receive sensitivity
 - Advanced RF filtering and blocking for enhanced channel spacing
 - Best path sequencing for advanced multipath resistance
 - Enhanced bursting
 - Enhanced compression and fast frames
 - Dynamic frequency selection (DFS) - DFS2 in final testing
 - Transmit power control (TPC and aTPC)
- ⇒ Performance
 - 802.11a/b/g standard 20MHz Channel
 - 26+ Mbps uncompressible data standard mode
 - 43+ Mbps uncompressible data turbo mode
 - 60+ Mbps compressible data standard mode

StarV3 Cloaking Mode

- 5MHz channel spacing - over 6 Mbps uncompressible data
- 10MHz channel spacing - over 13 Mbps uncompressible data

Maximum Link Distance 230km

Processor

- ⇒ Intel XScale IXP425 network processor operating at 533MHz

Management

- ⇒ Remote firmware upgrade with full configuration preservation
- ⇒ Access unit, client, and network management displays and tools
- ⇒ Diagnostic tools including ping and throughput testing
- ⇒ Beacon real-time traffic monitor
- ⇒ Push button hardware reboot with restore to factory defaults functionality
- ⇒ SNMP Support and Statistics

Power Supply System

- ⇒ Autosensing 120/240 VAC, 50/60Hz
- ⇒ 48 VDC input
- ⇒ World power system enabled
- ⇒ Solar systems available in turn-key configurations

On-Board Protection Systems

- ⇒ Transient/overvoltage protection for both power and Ethernet sub-systems

Environmental

- ⇒ Extended operating temperature: -20 to +70 C
- ⇒ Humidity: 5% to 95% non-condensing

Physical

- ⇒ 3.3 pounds
- ⇒ 9.3" x 9.25" x 4.05" (237mm x 235mm x 103mm)

Warranty

- ⇒ One year limited manufacturer defect warranty for all parts and labor

Current Branch

- Atheros Adaptive Radio
- Atheros Dynamic Turbo
- Atheros Auto channel selection support
- 802.11e QoS w/bursting and aggregation
- 802.11h (DFSv1 and DFSv2 for FCC3, ETSI, and MKK4)
- Dynamic WDS with full SuperAG and 802.11e support
- 802.11i

Certification



Please note the 900MHz radio module is NOT CE marked



Corporate Headquarters

1201 5th Avenue
Valemount, BC
V0E 2Z0 CANADA
tel. 250-566-2323
valemount.networks@gmail.com

The Au400 is now available, please contact us for evaluation and volume pricing.

All contents copyright © 2007 Valemount Networks Corporation, all rights reserved. While every effort is made to ensure the information given in this document is accurate Valemount Networks Corporation does not accept liability for any errors which may arise. Specifications and other information in this document are subject to change without notice.